



SPIPNVR04

5 MEGAPIXEL IP NVR



USB BACKUP



MOTION
DETECTION



VGA



HDMI



OSD MENU

Key Features:

- 4 Channel 5 megapixel recording
- 4 Megapixel realtime recording (25fps) on all channels
- Auto port forwarding (no need for IP knowledge)
- E-MAP (see live viewing on E-map)
- Free DDNS account for dynamic IP address
- Individual channel instant playback on live viewing
- USB backup
- Motion detection
- User Friendly OSD (easy to use)
- 1 x audio input and 1 x output
- Mouse control
- HDMI & VGA video control
- Direct playback on iPhone/IPAD
- Fanless design - 0% noise
- Free CMS software (SPO ISS)
- Wrks on Google Chrome (Windows PC)

SPECIFICATIONS

Model Number	SPIPNVR04
IP Video Input	4 CH
Audio Input	1 CH, RCA (2.0 Vp-p, 1kΩ)
Incoming Bandwidth	24Mbps
HDMI Output	1
VGA Output	1
Audio Output	1 CH, RCA
Live View/Playback Resolution	5MP/4MP/3MP/1080P/ 960P/720P/VGA/D1/CIF
Recording Resolution	5MP/4MP/3MP/1080P/ 960P/720P/VGA/D1/CIF

(continued)

Realtime Playback at the Same Time	4CH, Max.4CH 1080P or 2CH 4MP
Hard Disk - SATA	1
Capacity	Up to 4TB for each disk
Network Interface	1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
Serial Interface	N/A
USB Interface	1 USB2.0 + 1 USB3.0
Alarm In	N/A
Alarm Out	N/A
POE Interface	4 independent 10 /100 Mbps PoE Ethernet interfaces
Max. Power	32W
Supported Standard	802.3af/at
Power Supply	48V, DC
Consumption	60W (Fully Configured)
Working Temperature	-10°C~55°C (14°F ~ 131°F)
Operating Temperature	0°C - +55°C
Working Humidity	10%-90%
Dimensions	43.6mm × 360.0mm ×254.3mm (1.72"×14.17"×10.01"),1U
Weight(without HDD)	1.5KG

